

500 Series, French Door Bottom Mount, 36", Brushed black steel anti-fingerprint, Total No Frost B36FD52SNB




- $\bullet \ \textbf{Freezer LEDLight provides you with better illumination for more}$
- · visibility in your fridge, at all times.
- Quicklce Pro System™: The industry's fastest refrigerator ice maker*, offers freshly filtered ice, replenished fast.
- UltraClarityPro® Water Filter: removes an astonishing >99.9% of sediments from your tap water.
- Ice and Water Dispenser with Tap Connection: Dispense water and ice
- Crescent shaped ice: enjoy classically shaped crescent shaped ice on demand

LIDOI-	02522507274
UPC code:	
Color: b	lack inox-antifingerprint
Panel Ready:	Not Possible
Silence Level:	40 dB(A) re 1pW
Fuse protection:	10 A
Volts:	110-120 V
Frequency:	60 Hz
ENERGY STAR®:	Yes
Power Cord Length:	66 15/16 "
Plug type:	120V-3 prong
Required Cutout Size (HxWxD) (in):	x
Product Packaging Dimensions (HxWxD):	73.03 x 39.29 x 35.98
Total Unit Gross Capacity - AHAM:	26.0 Cu Ft
Refrigerator Gross Capacity:	18.0 Cu Ft
Freezer Gross Capacity:	8.0 Cu Ft
Net Weight:	326.000 lbs
Gross Weight:	




BORPLFTR55 Ultraclarity PRO water filter
FPETHKT50 Fresh Protect Ethylene Starter Kit
FPETHRF50 Fresh Protect Ethylene Refill Kit

500 Series, French Door Bottom Mount, 36", Brushed black steel anti-fingerprint, Total No Frost B36FD52SNB




B: Add 1" (25 mm) for fixed spacers on back

Measurements in inches (mm)




A: Add 1/4" (6 mm) with front leveling feet fully extended

Measurements in inches (mm)




Drawers can be pulled out with door open to 90°
Drawers can be taken out with door completely opened

measurements in inches (mm)







Leave ½" (12.7) gap at the top and 1" (25.4) behind the refrigerator for proper ventilation.

It is recommended that you do not install the refrigerator near a heat source such as an oven or a range.