




The ultra slim design of TT hides quietly within cabinetry and extends less than 2" below the edge. When called to action, the horizontal visor effortlessly pulls out to provide added air capture during cooking. TT design is ideal for smaller kitchens or where under-cabinet space is limited. The 400 CFM blower provides more than adequate power for everyday cooking. The 3 speed blower and LED lighting are operated with modern electronic push button controls, which are out of sight and behind the visor when idle.





	ETT424S1	ETT430SS	ETT436SS	
Α	23 1/2"	30''	35 1/3"	
В	6 1/9"			
С	11"			
D	1 4/7"			
E	10 2/7"			
F	18 1/9"	24 1/2"	30"	
G	6"			

TT



SPECIFICATIONS





	24" UNIT	30" UNIT	36" UNIT		
Model:	ETT424S1	ETT430SS	ETT430SS		
Dimensions:	24"	30''	36''		
Blower type (internal):	\$40am				
Blower performance:					
Speed 1	110 CFM				
Speed 2	190 CFM				
Speed 3	290 CFM				
Boost	400 CFM				
Noise (sones): At working speed	Min: 0.67, Max: 7.46				
Finish:	Stainless Steel				
Controls:	Hidden electronic push controls				
Illumination:	2 LED , 2.1 W				
Filter type:	1 Anodized Dishwasher Safe Aluminum Mesh Filters				
Duct transition:	Round				
Installation type:	Available in recirculating version				
Electrical:	120 V 60 Hz	120 V 60 Hz	120 V 60 Hz		
	PLUG TYPE B	PLUG TYPE B	PLUG TYPE B		
KITS:					
Recirculating Kit:	F00539				
CFM Reduction Kit:	KIT02736				

^{*}The product images shown are for illustration purposes only and may not be an exact representation of the product.