QUICK REFERENCE GUIDE > WB24SDEB2

Warming Drawer, 24"

Series 9 | Minimal

Black



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Minimal design.

- A companion product, designed to match with other Minimal style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	5 1/2 "
Width	23 ⁷ / ₁₆ "
Depth	22 ⁵ / ₁₆ "

FEATURES & BENEFITS

Complementary design

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy to clean

<>

Easy to use

Handle-free, push-to-open with capactive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Capacity

Cappuccino cups	20
Fenrasso cups	12

Maximum allowable weight	55lb
Place settings	6
Jsable depth	16
Jsable height	3
Jsable width	21

Cleaning

Easy clean smooth-glass base

Controls

Audio fe	edback	•
Automat	ic timers	30', 45', 1h, 2h, 4h, 6h
Delayed	start	•
Interior I	ght	LED
Intuitive	capacitive touch	•
On/Off i	ndicator	•
Pre-set h	eating functions	•
Push-to-	open drawer	•
Sabbath	mode	•
Standby	mode	•

Functions

unctions	
Cups	
Dehydrate	
Number of functions	
Plates	
Rapid proof	
Slow cook	
Warm	

QUICK REFERENCE GUIDE > WB24SDEB2 Date: 01.04.2021 > 2

Performance

Heated glass base and fan

Low temperature cooking

Temperature levels

6

Temperature range

95°F-185°F

Power requirements

Amperage 10A

Maximum power 810W

Power cord length 70

Power outlet 3-prong grounding-type

Supply frequency 60Hz

Supply voltage 110V

Product dimensions

Adjustable front door panel to

Depth $22\frac{5}{16}$ "
Height $5\frac{1}{2}$ "

Width 23 ⁷/₁₆ "

Safety

Automatic turn off after 12

Full extension telescopic

Warranty

Parts and labour 2 years

SKU 82141

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Guide D'Utilisation



Service & Warranty Booklet



Installation Guide



Guide D'Installation



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com