Warming Drawer, 30"

Series 9 | Minimal

Black



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Minimal design.

- A companion product, designed to match with other Minimal style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

10 ¹¹ / ₁₆ ′
29 ¹⁵ / ₁₆ ′
22 ⁵ / ₁₆ ′

FEATURES & BENEFITS

Complementary design

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy to clean

<>

Easy to use

Handle-free, push-to-open with capactive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories

Wire shelf

Capacity Accessory rack maximum Cappuccino cups Espresso cups Maximum allowable weight Place settings

Place settings	16
Usable depth	16
Usable height	9
Usable width	27

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback	•
Automatic timers	30', 45', 1h, 2h, 4h, 6h
Delayed start	•
Interior light	LED
Intuitive capacitive touch	•
On/Off indicator	•
Pre-set heating functions	•
Push-to-open drawer	•
Sabbath mode	•
Soft close drawer	•
Standby mode	•

Functions

Cups Dehydrate

1

42lb

24

54

55lb

FISHER & PAYKEL

QUICK REFERENCE GUIDE > WB30SDEB1

Number of functions	6
Plates	•
Rapid proof	•
Slow cook	•
Warm	•

Performance

Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
Temperature range	95°F-185°F

Power requirements

10A
810W
70
3-prong grounding-type
60Hz
110V

Product dimensions

Adjustable front door panel to	•
Depth	22 ⁵ / ₁₆ "
Height	10 ¹¹ / ₁₆ "
Width	29 ¹⁵ / ₁₆ "

Safety

Automatic turn off after 12

Full extension telescopic

WarrantyParts and labour2 yearsSKU82113

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

<u> </u>	User Guide
⊥	Guide D'Utilisation
<u>↓</u>	Service & Warranty Booklet
<u>↓</u>	Installation Guide
<u>+</u>	Guide D'Installation

24/7 A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 Wwww.fisherpaykel.com