

Color Variants

BO481613

Stainless steel-backed full glass door Width 76 cm

Included accessories

- x enamel baking trav. suit. pyrolitic clean.
- x rotary spit.
- x grill shelf.
- x arill tub with arid.
- x pluggable meat probe.

Optional accessories

BA018165

Pull-out system

BA028115

Baking tray, enameled

BA038165

Wire rack, chromium-plated

BA058115

Heating element for baking stone and cast-iron roaster

BA058133

Baking stone

BS020002

Pizza peel, additional set of 2

GN340230

Product Variants

Controls at the top

BO480613 Oven 400 series Stainless steel-backed full glass door Width 76 cm right-hand

BO481613 Oven 400 series

Stainless steel-backed full glass door

Width 76 cm

left-hand

Controls at the top

Handleless door / automatic door opening Pvrolvtic system 17 heating methods, with core temperature probe, rotisserie spit and baking stone function Automatic programmes Core temperature probe with estimation of cooking time TFT touch display Panel-free appliance with surface

control module Electronic temperature control from 30

°C to 300 °C Net volume 110 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat, Top heat, 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill, Compact grill, Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes (incl. core temperature probe). Personalisation of automatic

programmes. Information key with use indicators. Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.

Automatic programmes.

Rotisserie spit.

Baking stone socket.

Actual temperature display.

Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. 2 x 10 W halogen light on the side. Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check; homeconnect.com.

Safety

Thermally insulated door with quadruple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.

Product Features

Cooking mode

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

Integrated Cleaning system

Self Clean

Interior Lights - cavity 1

Pull-out system

Accessor

Timer settings

Alarm, Off, On, timer

x enamel baking tray, suit. pyrolitic clean, x rotary spit, x grill shelf, x grill tub with grid, x pluggable meat probe

Bake Element Wattages cavity 1 (W) 1700

Broil Element Wattages cavity 1 (W) 3900

Convection Element Wattages cavity 1 (W)

1900

Microwave Wattages (W)

Drawer wattage (W)

Consumption and connection features

UPC code

825225957409

Product color

Alternative colors available

Energy source Electric

Watts (W) 5520

Current (A)

Volts (V) 208/220-240

Frequency (Hz)

Approval certificates

CSA, ETL, UL

Power cord length (in)

47 1/4

Power cord length (cm)

Plug type

fixed connection

26 3/16 " x 28 1/2 " x 21 11/16 "

Required cutout size (HxWxD) (mm) 665-665 x 724-724 x 550

Overall appliance dimensions (HxWxD) (mm)

670 x 752 x 547

Product packaging dimensions (HxWxD) (in)

33 7/8 x 33 7/16 x 29 15/16 Product packaging dimensions

(HxWxD) (mm)

860 x 760 x 850

Net weight (lbs) 172.000

Net weight (kg)

Gross weight (lbs) 186,000

Gross weight (kg)

2020-09-03 Page 1

When planning a corner solution, pay attention to the 90° door opening

The mains socket needs to be planned outside the built-in niche.

Connection

Total connected load 5.5 KW.

Total Amps: 25 A.

208 / 220 - 240 V / 60 Hz.

Connection cable 1.2 m without plug. Power consumption standby/display off 0.5 W.

Power consumption standby/network


Please check the user manual for how to switch off the WiFi module.



BO481613 Oven 400 series Stainless steel-backed full glass door Width 76 cm left-hand

2020-09-03 Page 2

Controls at the top



* 8" (200 mm) in conjunction with BA 0

