



**BOP251612**  
**200 series Oven**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**left-hand**

Flush installation  
 Pyrolytic system  
 13 heating methods with core temperature probe and baking stone function  
 Automatic programmes  
 Core temperature probe with estimation of cooking time  
 TFT touch display  
 Panel-free appliance with surface control module  
 Electronic temperature control from 30 °C to 300 °C  
 Net volume 76 litres

#### Heating methods

Hot air, Eco hot air, Top + bottom heat, Top heat, Bottom heat, Hot air + bottom heat, Full surface grill + circulated air, Full surface grill, Compact grill, Baking stone function, Roaster function, Dough proofing, Defrosting.

#### Handling

Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes (incl. core temperature probe).  
 Personalisation of automatic programmes.  
 Information key with use indicators.  
 Side-opening door opens up to 110° angle.

#### Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.  
 Automatic programmes.  
 Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.  
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.  
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

#### Safety

Thermally insulated door with quintuple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
 Gaggenau enamel.  
 Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

#### Product Features

##### Cooking mode

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat

##### Integrated Cleaning system

Self Clean

##### Interior Lights - cavity 1

1

##### Pull-out system

Accessory

##### Timer settings

Alarm, Off, On, timer

x enamel baking tray, suit. pyrolytic clean, x grill shelf, x grill tub with grid, x pluggable meat probe

##### Bake Element Wattages cavity 1 (W)

1300

##### Broil Element Wattages cavity 1 (W)

3000

##### Convection Element Wattages cavity 1 (W)

2100

##### Microwave Wattages (W)

Drawer wattage (W)

#### Consumption and connection features

##### UPC code

825225957447

##### Product color

Alternative colors available

##### Energy source

Electric

##### Watts (W)

4030

##### Current (A)

17

##### Volts (V)

208/220-240

##### Frequency (Hz)

60

##### Approval certificates

CSA, ETL, UL

##### Power cord length (in)

39 3/8

##### Power cord length (cm)

100

##### Plug type

fixed connection

23 1/4" x 22 1/16" x 21 11/16"

##### Required cutout size (HxWxD) (mm)

590-590 x 560-560 x 550

##### Overall appliance dimensions (HxWxD) (mm)

595 x 590 x 547

##### Product packaging dimensions (HxWxD) (in)

30 11/16" x 26 3/4" x 29 15/16"

##### Product packaging dimensions (HxWxD) (mm)

770 x 710 x 650

##### Net weight (lbs)

123.000

##### Net weight (kg)

55.693

##### Gross weight (lbs)

132.000

##### Gross weight (kg)

59.9

2020-09-03

Page 1

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

#### Connection

Total connected load 4.0 KW.

Total Amps: 17 A.

208 / 220 - 240 V / 60 Hz.

Connection cable 1.0 m without plug.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.4 W.

Please check the user manual for how to switch off the WiFi module.

#### Color Variants

BOP251612

Full glass door in Gaggenau Metallic

Width 60 cm

#### Included accessories

x enamel baking tray.

suit. pyrolytic clean.

x grill shelf.

x grill tub with grid.

x pluggable meat probe.

#### Optional accessories

BA016165

Pull-out system

BA026115

Baking tray, enameled

BA036165

Wire rack, chromium-plated

BA056115

Heating element for baking stone and cast-iron roaster

BA056133

Baking stone

BA226105

Broil pan, enameled

BS020002

Pizza peel, additional set of 2

GN340230

#### Product Variants

BOP250612

200 series Oven

Full glass door in Gaggenau Metallic

Width 60 cm

right-hand

# GAGGENAU

BOP251612  
200 series Oven  
Full glass door in Gaggenau Metallic  
Width 60 cm  
left-hand

2020-09-03  
Page 2

