



C|282610
Flex induction cooktop 200 series
Stainless steel frame
Width 80 cm

Sturdy stainless steel frame
Flex function for combining the rectangular cooking areas
Free positioning of cookware inside combined cooking areas
Cooking sensor function for temperature control in pots
Frying sensor function for temperature control in pans
Twist-Pad control with removable magnetic knob
Easy control of all functions with bicoloured display

Color Variants

C|282610
Stainless steel frame
Width 80 cm

Optional accessories

CA051300
Teppan Yaki made of multi ply material
CA060600
Cooking sensor for temperature regulation within pots
CA230100
Black magnetic knob for induction cooktop 200 series
GP900001
Stainless steel frying sensor pan.
GP900002
Stainless steel frying sensor pan.
GP900003
Stainless steel frying sensor pan.
GP900004
Stainless steel frying sensor pan.

Cooking zones

2 flex induction cooking areas 19x24 cm (2200 W, with booster 3600 W), linked together 38x24 cm (3300 W, with booster 3600 W).
1 induction cooking zone ø 28 cm (2600 W, with booster 3700 W).
1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

Handling

Twist-Pad control with removable magnetic knob.
User friendly control with bicoloured display (white / orange).
Cooking zone and cooking area marking.
Electronic power control in 17 stage 1,1..2..9.

Features

Flex function for rectangular cooking areas.
Cooking sensor function (in use with cooking sensor CA 060 600).
Frying sensor function.
Booster function for pots.
Booster function for pans.
Keep warm function.
Stopwatch.
Cooking timer for up to 99 minutes.
Short-term timer.
Options menu.
Power management.

Safety

Main switch.
Operation indicator.
Pot detection.
Digital 2-step
Child lock.
Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. The wok pan WP 400 001 cannot be used with this appliance.
Immersion depth 107 mm.
Intermediate shelf is recommended.
Appliance must be fixed from underneath.
Cooktop clamping range: 20 - 40 mm.
Appliance weight: approx. 21 kg.

Connection

Total connected load 6.2 kW.
Connecting cable 1.0 m without plug.

Product Features

Knob Material
Full metal
Sealed Burners
No
Burners with booster
All
Type of grate
Natural Gas Connection Rating (BTU)
LP Gas Connection Rating (BTU)
Dimension of 1st heating element (in)
Power of heating element (W)
Power of 1st burner (BTU)
Dimension of 2nd heating element (in)
Power of 2nd heating element (W)
3.3
Power of 2nd burner (BTU)
Dimension of 3rd heating element (in)
Power of 3rd heating element (W)
Power of 3rd burner (BTU)
Dimension of 4th heating element (in)
Power of 4th heating element (W)
Power of 4th burner (BTU)

Consumption and connection features

UPC code
825225919834
Variant color
Black
Energy source
Electric
Gas type
Alternative gas type
Watts (W)
7200
Current (A)
30
Volts (V)
208-240
Frequency (Hz)
60
Approval certificates
CSA, FCC
Power cord length (in)
37"
Power cord length (cm)
96
Plug type
no plug
Required cutout size (HxWxD) (in)
4 1/4" x 31" x 19 5/8"
Required cutout size (HxWxD) (mm)
107 x 786-788 x 498-500
Minimum distance from counter front (in)
2 1/2"
Minimum distance from rear wall (in)
2 3/8"
Overall appliance dimensions (HxWxD) (in)
1/8"+4 1/4" x 31 3/4" x 20 1/2"
Overall appliance dimensions (HxWxD) (mm)
107 x 804 x 520
Product packaging dimensions (HxWxD) (in)
7 1/16" x 36 5/8" x 26 5/8"
Product packaging dimensions (HxWxD) (mm)
172 x 925 x 680
Net weight (lbs)
45
Net weight (kg)
20.629
Gross weight (lbs)
54
Gross weight (kg)
24.4
Total number of cooktop burners
4

2020-03-29

Page 1