

Color Variants RY492701 With fresh cooling Fully integrated

Included accessories 1 x egg box with lid.

1 x ice cube scoop.

**Optional accessories** RA450000 Mechanical particle filter RA450010 Activated charcoal filter for water filter system including saturation indicator

Required installation accessories RA460000 Installation kit for side-by-side installation (for connecting any two columns) RA460010 Additional side heating element

Installation Accessories RA421912 Stainless steel door panel with handles RA425110 Handle bar, stainless steel, long RA425910 Handle bar. stainless steel, short RA460030 Connecting element for vertically split fronts (for fridge-freezer combination with one door) RA461910 Ventilation grille stainless steel

RY492701 Vario fridge-freezer combination 400 series With fresh cooling Fully integrated Niche width 91.4 cm, Niche height 213.4 cm With two doors

Stainless steel interior Generous lighting concept Solid aluminium door racks Net volume 557 litres Integrated ice maker with fixed inlet water connection One motorised glass shelf, adjustable when fully loaded One asymmetricly split glass shelf Fully extendable freezer drawer with practical divider

### Handling

Electronic temperature control with digital display.

#### Technical Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation. Rest mode certified by Star-K. Open-door and malfunction alarm.

#### Cooling

No-Frost technology with fast cooling. 2 safety glass shelves, 1 of which is motorised. 1 asymmetrically split safety glass shelf, with manual height adjustment. 2 fully extendable drawers with transparent front. Bright interior lighting with light pillars. 4 height adjustable door racks, 2 of which are extra deep. 2 door racks with transparent front flap.

Fresh cooling

No-frost technology. 1 full width fully extendable fresh cooling drawer with transparent front, manually controllable.

# Freezing

Net volume 165 litres. No-frost technology with fast freezing. 4-star freezer compartment. 2 fully extendable drawers. Interior lighting with 2 spots.

#### Ice maker

Integrated in the freezer compartment, with fixed inlet water connection. Can be switched off. Ice cube production approx. 1.4 kg/24 h

Removable ice storage container with approx. 3 kg capacity.

#### Consumption data

Energy consumption 589.84 kwh/year. Energy consumption 1.616 kwh/24 h. Noise level 41 dB (re 1 pW).

### Planning notes

Flat hinge Door opening angle of 115°, fixable at 90° Max. door panel weight: Each door 57 kg. Drawer 10 kg. Shut-off valve for water connection must be planned next to the appliance and always be accessible. If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

### Connection

Total connected load 0.588 kW. Connecting cable 118,1" (3.0 m) with plug. Water inlet. Water pressure 2 to 8 bar.

**Product Features Multi-Flow Air Tower** Yes

Number of compressors

Number of independent cooling systems


## Eco Mode Yes

SUPERFREEZE
Yes
Number of Door Bins - Freezer
Adjustable Door Bins - Freezer
Tilt-Out Door Bins - Freezer
Number of shelves - Freezer
Adjustable Door Bins - Freezer
Shelf Material - Freezer
Door hinge
left and right
Reversible Door Hinge
No

#### Consumption and connection features UPC code 825225803140 Variant color Not applicable Panel ready Installation Type N/A Silence level (dBA) 41 Watts (W) 588 Current (A) Volts (V) 120 Frequency (Hz) Energy consumption (kWh/yr) 589.8 Energy Star® qualified Approval certificates ETL. ETL Power cord length (in) 118,1' Plug type 120V-3 prong Appliance dimensions (h x w x d) inch 83 3/4 " x 35 3/4" x 24 Required cutout size (HxWxD) (in) 84" x 36" x 24 3/4 Appliance Width (in) 35 3/4" Height (in) 83 3/4 Depth (in) 24 Product packaging dimensions (HxWxD) (in) 89.37 x 39.37 x 29.52 Total unit gross capacity (cu. ft.) - AHAM 19.6 Net weight (lbs) 491 Gross weight (lbs) 534 2019-09-24

Page 1





Page 2

Wall clearance RB 492/RY 492 36" (914) Niche 7/16" (11) 18<sup>1</sup>/8" (460) (256) \_9<sup>1</sup>/4"\_ (236) স্য 16<sup>7</sup>/8" (428) 24" (610) • (610) <sup>7</sup>/16 (11) 20<sup>7</sup>/8 (530) (426) : 90° 1<sup>5</sup>/<sub>16</sub><sup>°°</sup> (49) <sup>3</sup>/4<sup>°°</sup> (19) 115° 90° <sup>3</sup>/4" 1<sup>5</sup>/1 (19) (49) <sup>3</sup>/4" (19) The drawing is based on a cabinet panel width of  $^{3}/^{\ast}$  (19 mm) and a Gaggenau cabinet handle height of 15'16'' (49 mm).

