



## 30" ELECTRIC RADIANT COOKTOP WITH ELECTRONIC TOUCH CONTROL

JEC4430BS – 31" x 5<sup>5</sup>/<sub>16</sub>" x 22<sup>3</sup>/<sub>16</sub>"JEC4430BB – 30<sup>7</sup>/<sub>8</sub>" x 5<sup>5</sup>/<sub>16</sub>" x 21<sup>11</sup>/<sub>16</sub>"


## PRODUCT DIMENSIONS



TOP VIEW



FRONT VIEW



SIDE VIEW

MODEL #		JEC4430B	
		in	cm
A	Overall width		
	Euro-Style Stainless (including trim)	31	78.7
	Floating Glass	30 <sup>7</sup> / <sub>8</sub>	78.4
B	Overall depth		
	Euro-Style Stainless (including trim)	22 <sup>3</sup> / <sub>16</sub>	56.4
	Floating Glass	21 <sup>11</sup> / <sub>16</sub>	55.1
C	Width of recessed cooktop	28 <sup>15</sup> / <sub>16</sub>	73.5
D	Height of recessed cooktop	3 <sup>3</sup> / <sub>4</sub>	9.6
E	Height of recessed cooktop including conduit	5 <sup>5</sup> / <sub>16</sub>	13.5
F	Height of cooking surface		
	Euro-Style Stainless	5 <sup>5</sup> / <sub>16</sub>	0.8
	Floating Glass	1 <sup>1</sup> / <sub>4</sub>	0.6
G	Depth of recessed cooktop	20 <sup>1</sup> / <sub>4</sub>	51.5


**IMPORTANT:** Dimensional specifications are provided for planning purposes only.Do not make any cutouts based on this information. Refer to the Installation Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.

All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.


## 30" ELECTRIC RADIANT COOKTOP WITH ELECTRONIC TOUCH CONTROL

JEC4430BS – 31" x 5<sup>5</sup>/<sub>16</sub>" x 22<sup>3</sup>/<sub>16</sub>"JEC4430BB – 30<sup>7</sup>/<sub>8</sub>" x 5<sup>5</sup>/<sub>16</sub>" x 21<sup>11</sup>/<sub>16</sub>"


## OPENING/CLEARANCE DIMENSIONS



FRONT VIEW



SIDE VIEW



TOP VIEW

MODEL #		JEC4430B	
		in	cm
A	Width of combustible area above cooking surface (min.)	30	76.2
B	Width from cooktop to fixed wall or other combustible material (min.)	1	2.5
C	Width to outer edge of outlet (max.)	9	23.0
D*	Height to bottom of uncovered wood or metal cabinet above cooking surface (min.)	30	76.2
E	Height to bottom of uncovered wood or metal cabinet (min.)	18	45.7
F	Height to top edge of outlet (min.)	7	17.8
G	Depth of upper cabinet	13	33.0
H	Depth from cutout to wall (min.)	1	2.5
I	Width of cutout (recommended)	29½	74.9
J	Depth of cutout (recommended)	20½	52.0
K	Depth from cutout to front of countertop	2⅝	6.7
e	Recommended electrical access location		

\*Dimension can be reduced by 6" (15.2 cm) when bottom of wood or metal cabinet is covered by not less than ¼" (0.6 cm) flame retardant millboard covered with not less than No. 28 MSG sheet metal, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

If installing a hood or microwave hood combination above the cooktop, follow the hood or microwave hood combination instructions for dimensional clearances above the cooking surface.

## ELECTRICAL REQUIREMENTS

A 3-wire or 4-wire, single phase, 120/240 volt, 60 Hz., AC only electrical supply is required on a separate, 40-amp circuit fused on both sides of the line. 48" (121.9 cm) of ½" (1.3 cm) I.D. flexible cable is provided.

## LOCATION REQUIREMENTS

- To ensure cooktop base clearance, cabinet side walls need to be wider than the cutout.
- If cabinet has a drawer, allow a 5½" (14.0 cm) minimum clearance between countertop and top of drawer.

## COOKTOP OVER SINGLE WALL OVEN INSTALLATION REQUIREMENTS

- For approved model number combinations, refer to the under counter label on the bottom of the cooktop burner box.
- To install a cooktop over a single wall oven, refer to page 3.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only.

**Do not make any cutouts based on this information.** Refer to the Installation Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

## SINGLE WALL OVEN AND COOKTOP COMBINATIONS

For the approved model number combinations, refer to the under counter label located on top of the oven chassis and on the bottom of the cooktop burner box.

## APPROVED MODEL NUMBER COMBINATIONS

## SINGLE WALL OVENS

30-Inch: JJW3430D, JJW2430D

27-Inch: JJW2427D

## INDUCTION COOKTOPS

36-Inch: JIC4536X

30-Inch: JIC4430X

## GAS COOKTOPS

36-Inch: JGC7636B, JGC1536B


30-Inch: JGC7530B, JGC1530B

## ELECTRIC COOKTOPS


36-Inch: JEC4536B, JEC3536B

30-Inch: JEC4430B, JEC3430B

## OPENING/CLEARANCE DIMENSIONS



**FRONT VIEW –  
UNDER COUNTER INSTALLATION**  
(with cooktop installed above)



**SIDE VIEW –  
UNDER COUNTER INSTALLATION**  
(with cooktop installed above)

MODEL #	JJW3430D JJW2430D		JJW2427D	
	in	cm	in	cm
<b>A</b>	Width of cabinet (min.)		30	76.2
<b>B</b>	Width of cutout (recommended)		28½	72.4
<b>C</b>	Oven trim overlap		⅝	1.6
<b>D</b>	Top of countertop to floor		36	91.4
<b>E</b>	Top of countertop to bottom of cutout			
	Induction cooktop combination		31⅜	79.7
	Gas cooktop combination		31⅜	79.7
<b>F</b>	Electric cooktop combination		31⅜	79.7
	Height of cutout (recommended)		27¾	70.5
<b>G</b>	Bottom of cutout to floor			
	Induction cooktop combination		4⅝	11.7
	Gas cooktop combination		4⅝	11.7
<b>H</b>	Electric cooktop combination		4⅝	11.7
	Depth of cabinet (min.)		24	61.0
<b>e</b>	Recommended junction box location			
<b>g</b>	Recommended gas supply line location for gas cooktop			

**NOTE:** For under counter installation, the junction box should be located in the adjacent right or left cabinet. Drill a 1" (2.5 cm) minimum diameter hole in an upper corner of the side wall for access to the junction box.

## CABINET REQUIREMENTS

**NOTE:** When using under counter installation, check cabinet manufacturer's specifications to verify fit.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only.

**Do not make any cutouts based on this information.** Refer to the Installation Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.