

# CBS 2092G

Freestanding / Semi Built-in

# LIEBHERR



## Refrigeration and Freezing



home.liebherr.com

### CBS 2092G

Energy consumption (kWh / y)	550
Estimated Yearly Energy Cost* in US \$	77
Sound rating** dB(A)	42
Refrigerator capacity cu.ft. (l)	12.9 (365)
BioFresh compartment cu.ft. (l)	2.4 (69)
Freezer capacity cu.ft. (l)	6.0 (170)
Electronic control	Display, touch electronic
Defrost type	Automatic
Interior light	LED light column / LED ceiling
Number of shelves	4
Number of door racks	6
Number of BioFresh drawers	2
Number of freezer drawers	2
Refrigerator Temperature range °F (°C)	+37°F to +45°F (+3°C to +7°C)
Freezer Temperature range °F (°C)	+7°F to -17°F (-14°C to -27°C)
Water filter	Yes
Ice maker	Fixed water connection
Ice cube output lbs. (kg.)	3.1(1.4)
Ice cube stock lbs. (kg.)	6(2.7)
Door hinges	left/right
<b>Product dimensions</b>	
in inch (H / W / D)	80 5/16" / 35 7/8" / 24 1/4"
in cm (H / W / D)	203.9/91/61.5
<b>Cut out dimensions</b>	
in inch (H / W / D)	80 1/2" / 36" / 24 1/16"
in cm (H / W / D)	204.5/91.5/61
Net weight lbs. (kg)	377.0 (171.0)
Voltage V / Hz	115/60

### Accessories

**Water Filter** 9880980/7440002 / 9883057

**Top Ventillation Grill 84" cabinets, French Door** 9900199

### Features

#### Bio Fresh

Preserve just-bought groceries for optimum food freshness, while sealing in flavors and maintaining essential vitamins and minerals.

#### Duo Cooling

Lengthen the shelf life and preserve the flavor of your foods with a dual refrigeration system that creates ideal conditions in both the refrigerator and freezer.

#### Ice Maker

Liebherr's automatic IceMaker produces perfect ice cubes and keeps a constant supply on hand for every occasion.

#### Telescopic Rails

Store food securely within reach thanks to fully extendable pull-out drawers. The SoftTelescopic system provides convenient and reliable self-retraction with soft closing.

\* Energy Cost will depend on utility rates and use. Estimated energy cost based on a national average electricity cost of 14 cents per KWh.

\*\* Noise output – according to EN 60704-3

# Diagrams

### Product Dimensions

**Front View Dimensions:**

- Top of refrigerator door: 2" (50 mm)
- Refrigerator door height: 45 1/2" (1156 mm)
- Centerline between Refrigerator doors and Freezer drawer: 13 11/16" (348 mm)
- Centerline between Freezer drawers: 16 11/16" (424 mm)
- Bottom clearance: 4"

**Side View Dimensions:**

- Top depth: 5 9/16" (141.5 mm)
- Depth: 1 1/2"
- Height: 79 13/16" (2027 mm)
- Internal depth: 1 11/16" (43 mm)
- Internal depth: 2 1/4" (57 mm)
- Internal depth: 13 3/8" (340 mm)

**Door Swing View Dimensions:**

- Door width: 35 13/16" (910 mm)
- Door height: 41" (1041 mm)
- Clearance from wall: 22 1/16" (561 mm)
- Clearance from wall: 13 1/2" (343 mm)
- Door swing angle: 145°
- Bottom hinge angle: 90°

Allow door swing clearance at locations next to a wall.

The refrigerator door must open to a minimum of 90° to allow the crispers to open and the shelves to be removed.

Height can be increased by 1-1/2" (40 mm) by turning the levelling feet at the front and the height adjustable roller units at the appliance rear.

### Semi built-in look - Cut out dimensions

The appliance can be used freestanding or semi built-in. If semi built-in, consider the cabinet opening dimensions specified below.

Minimum opening height for the french door 36" model is 80-1/2" to accommodate the top mounted hinges.

The requirements for water supply and electrical outlet are the same for both applications.

**IMPORTANT**  
Do not install the shut-off valve for the water supply behind the appliance.

**Water line opening:** 7-5/8" (195 mm) x 15-3/8" (390 mm)

**Water supply line:** Free length at least 31 - 1/2" (800 mm)

**Dimensions:**

- Opening height: 80-1/2" (2045 mm)
- Opening width: 36" (914 mm)
- Depth: 24" (610 mm)
- Top clearance: 40" max.
- Right side clearance: 78" max.
- Overall height: 82" max.

**IMPORTANT**  
With 24" depth cabinets, the water line opening must be in the location as shown as there will not be room to route a water line behind the appliance for risk of pinching. Also, for this cabinet depth the electrical outlet cannot be behind the unit or the unit will not be able to be pushed all the way back into the opening. With cabinets deeper than 24" there is room to fit the pipe behind the appliance and the wall so there are no requirements for the water line lead out position.

### Ventilation Requirements

CBS 20 appliances don't need any ventilation openings in the cabinet. The required airflow is directed through the toe kick area.

It is important to use the provided cover grille for the ventilation opening. This opening must not be covered with a cabinet base.

Subject to modification. For up-to-date information, visit [home.liebherr.com](http://home.liebherr.com). Specifications are for planning purposes only. For more detailed information, refer to installation instructions or Design Guide.