

DA 1280 30-inch built-under ventilation hood with energy-efficient LED lighting and sliding switch for simple operation.




- Minimalist design 30 (760) in (mm) wide space saving solution
- Powerful ?? on the booster setting
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean Miele CleanCover
- Suitable for every home vented or recirculating

EAN: 4002515774403 / Material number: 10451490 / Old Material Number: 28128055USA

Construction type	
Built-under ventilation hood	•
Operating modes	
Recirculated mode	Convertible
	DKF 18-900
OdorFree charcoal filter (order separately)	DKF 18-900
Design	Ctainless atasl
Color	Stainless steel
Customization possible on request	
Control panel Recessed knob controls	•
	-
Power levels (number excl. Intensive)	3
Slide switch	•
Cleaning convenience	
Easy-to-clean CleanCover hood liner	•
Filter system	
Number of dishwasher-safe stainless-steel grease filters	3
Lighting	
LED	
Number x W	2 x 3 W
Light intensity in Lx	275 lx
Color temperature in K	3000 Kelvin
Blower	
Single-action blower	
AC motor	•
Extraction	
Extraction Air throughput	Values upon request
	Values upon request
Air throughput	Values upon request 30 (760)
Air throughput Technical data	
Air throughput Technical data Canopy width in in.(mm)	30 (760)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm)	30 (760) 5 (125)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm)	30 (760) 5 (125) 19 3/4 (500)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg)	30 (760) 5 (125) 19 3/4 (500) 29 (12.9)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m)	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) • 0.28
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top Diameter of vent connection in in.(mm)	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top Diameter of vent connection in in.(mm) Installation template	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top Diameter of vent connection in in.(mm) Installation template Accessories supplied	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60 6 (150)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top Diameter of vent connection in in.(mm) Installation template Accessories supplied Recirculation deflector	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60 6 (150)
Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation notes Vent connection at top Diameter of vent connection in in.(mm) Installation template Accessories supplied Recirculation deflector Non-return flap	30 (760) 5 (125) 19 3/4 (500) 29 (12.9) 4 (1.5) 0.28 120 15 1 60 6 (150)



DA 1280 30-inch built-under ventilation hood with energy-efficient LED lighting and sliding switch for simple operation.



DA 1180, Stainless steel (installation drawing)