

## DAS 4720

### Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls



- Classic design – stainless-steel panel, 30" wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless steel grease filters
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516495925 / Material number: 11878520 / Old Material Number: 28S4720SUSA

<b>Construction type</b>	
Built-in ventilation hood	•
<b>Operating modes</b>	
Recirculated mode	Convertible
Recirculation conversion kit (order separately)	DUU 151
OdorFree charcoal filter (order separately)	DKFS 31-P, DKFS 31-R
<b>Design</b>	
Color	Stainless steel
<b>Control panel</b>	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
EasySwitch	•
Programmable Intensive switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Filter system</b>	
Number of dishwasher-safe stainless-steel grease filters	1
<b>Lighting</b>	
LED	•
Number x W	1 x 3 W
Light intensity in lx	330 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Extraction</b>	
Air throughput	Values upon request
<b>Safety</b>	
Safety shut-off	•
<b>Technical data</b>	
Canopy width in in.(mm)	29 7/8 (758)
Canopy height in in.(mm)	1 1/2 (36)
Canopy depth in in.(mm)	10 3/4 (273)
Minimum height above electric hobs in mm	24 1/8 (610)
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	36 (16.0)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Total connected load in kW	0.35
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Frequency in Hz	60

DAS 4720

Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls




EAN: 4002516495925 / Material number: 11878520 / Old Material Number: 28S4720SUSA

<b>Installation notes</b>	
Vent connection at top	•
<b>Accessories supplied</b>	
Non-return flap	•
<b>Optional accessories</b>	
OdorFree charcoal filter	Nein

## DAS 4720

### Built-in ventilation hood

for installation in narrow upper cabinets with EasySwitch controls



DAS4720 US, Installation drawings, VG USA

Extraction mode: the height of the wall unit and the cut-out dimensions must take into account any accessories fitted., Recirculation with recirculation conversion kit., Installation is also possible in a 600 mm wide unit., \* In this installation situation, the deflector plate is flush with the front edge of the housing unit carcass. If you wish to position the cooker hood further forward or further back (e.g. because it has a front panel), dimensions have to be adapted accordingly.