

KM 7730 FR
Induction Cooktop
with 4 round cooking zones



- Intuitive quick selection via number sequences – Smart Select
- Versatile – 4 cooking zones, 1 extra large with diameter of 11 in
- With a width of 30 5/8 (775) in (mm) and stainless steel frame for proud-mounting
- Shortest heating-up times – TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611493 / Material number: 12074200 / Old Material Number: 26773000USA

Type of heating	
Fuel type	Induction
Construction type	
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless steel frame	•
Proud installation	•
Ring features	
No. of rings	4
Number of cooking areas	0
Maximum number of pans	4
1st cooking zone/cooking area	
Position	front left
Type	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3000
Max. rating in W	2600
Max. TwinBooster power rating in W	3700
2nd cooking zone/cooking area	
Position	rear left
Type	Variable cooking zone
Size in mm	Ø 100-160
Max. Booster power rating in W	1700
Max. rating in W	1400
Max. TwinBooster power rating in W	2200
3rd cooking zone/cooking area	
Position	rear right
Type	Variable cooking zone
Size in mm	Ø 140-190
Max. Booster power rating in W	2500
Max. rating in W	1850
Max. TwinBooster power rating in W	3000
4th cooking zone/cooking area	
Position	front right
Type	Variable cooking zone
Size in mm	Ø 140-190
Max. Booster power rating in W	2500
Max. rating in W	1850
Max. TwinBooster power rating in W	3000
User convenience	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0	•
Operation via touchpad sensors	Smart Select
Keeping warm	•
Display color	Yellow
Permanent pan recognition	•
Pan/Pan-size sensors	•
Stop & Go function	•

KM 7730 FR
Induction Cooktop
with 4 round cooking zones



EAN: 4002516611493 / Material number: 12074200 / Old Material Number: 26773000USA

Recall function	•
Minute minder	•
Automatic switch-off for all rings	•
AutoBoost	•
Individual setting options (e.g. acoustic signal tones)	•
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions in mm (width)	30 5/8 (775)
Dimensions in mm (height)	3 1/8 (78)
Dimensions in mm (depth)	21 1/2 (544)
Casing height incl. connection box in mm	2 7/8 (71)
Cutout dimensions in mm (width) with surface-mounted installation	28 5/8 (724)
Cutout dimensions in mm (depth) with surface-mounted installation	20 1/2 (518)
Weight in kg	37 (17)
Total rated load in kW	6.60-7.60
Voltage in V	0
Frequency in Hz	60
Standard accessories	
Power cord	Yes