30" INTEGRATED OVER-AND-UNDER REFRIGERATOR/FREEZER WITH ICE MAKER AND INTERNAL DISPENSER - PANEL READY



IT-30CIID





FEATURES

Ready to be fitted with custom panels and handles to blend with cabinetry

Dual refrigeration keeps food fresher longer

Air purification system fights spoilage, odors

Internal water dispenser works with seamless design

Over-and-under refrigerator/freezer storage

Nano-coated spill-proof shelves for easy clean-up

Crispers and deli drawers in low-temp, high-humidity zones for optimum freshness

Smart-touch controls for streamlined access to more settings

Water-filtration system reduces contaminants, chlorine taste and odor

Automatic ice maker with "max ice" feature

Rigorously tested in our U.S. manufacturing facilities to ensure decades of use

Exceptional 24/7 support from Madison, WI-based Customer Care team

ACCESSORIES

Air Purification Cartridge

Egg Container

Stainless steel tubular handles

Stainless steel pro handles

Dual installation kits

Stainless steel front panels with tubular or pro handles

Stainless steel kickplate

Stainless steel side enclosure

Stainless steel top enclosure

Reduced toe kick divider for toe kicks from 2" to 3.875"

Replacement water filter

Accessories are available through an authorized Sub-Zero dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.



HANDLE ACCESSORIES



PRODUCT DETAILS

REFRIGERATOR

- · Three adjustable glass shelves
- · One stationary shelf
- · Crisper drawer with two adjustable dividers
- · Adjustable dairy compartment
- · Two adjustable door shelves
- · One stationary door shelf

FREEZER

- · Three adjustable drawer dividers
- · Removable ice container
- · Automatic ice maker




PRODUCT SPECIFICATIONS

Model	IT-30CIID
Dimensions	30"W x 84"H x 24"D
Door Clearance	28 1/2"
Drawer Clearance	18 3/8"
Weight	400 lb
Refrigerator Capacity	10.6 cu ft
Freezer Capacity	5 cu ft
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35–120 psi
Receptacle	3-prong grounding-type

ELECTRICAL

— LEFT SIDE OF OPENING → 41/2" ← 121/2" → (318) ↓ 41/4" (108) ↑ FLOOR ↑ 1/4" (6)

PLUMBING





INTERIOR VIEW




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

DIMENSIONS





STANDARD INSTALLATION



NOTE: $3^{1/2^{*}}$ (89) finished returns will be visible and should be finished to match cabinetry.

