


## FEATURES

- Advanced Dual VertiCross convection system for faster preheats and consistent cooking across all racks.
- Ten cooking modes for predictably delicious results (convection, roast, bake, broil, convection roast, baking stone, Gourmet, warm, proof and dehydration).
- Gourmet feature has menu of presets that automatically controls cooking of popular meals.
- Interactive color touchscreen for advanced cooking control.
- Heavy-duty stainless steel construction for decades of dependable service.
- Cobalt blue porcelain oven interiors.
- Large viewing, triple-pane windows and three halogen interior lights.
- Three adjustable oven racks per oven; two full extension and one standard.
- Hidden bake element and recessed broil element.
- Temperature probe and broiler pan.
- Self-clean, delayed start, timed cook and Sabbath features.
- Quiet-close doors with spring and damper hinge system.
- Standard or flush installation.
- Tubular handles match Wolf transitional products.



MODEL	
Transitional	DO30TM/S/TH




Interactive control panel.

## ACCESSORIES

- Bake stone kit (stone, rack and peel).
- Dehydration kit (racks and door stop).
- Single or set of three standard oven racks.
- Full-extension easy glide oven rack.
- 30" baking sheet.
- Temperature probe and broiler pan.

Accessories available through an authorized Wolf dealer. For local dealer information, visit the find a showroom section of our website, [wolfappliance.com](http://wolfappliance.com).



Model DO30TM/S/TH


## SPECIFICATIONS

PRODUCT	
Dimensions	29 <sup>7</sup> / <sub>8</sub> "W x 50 <sup>7</sup> / <sub>8</sub> "H x 23"D
Door Clearance	21 <sup>3</sup> / <sub>8</sub> "
Weight	466 lb
OVEN INTERIORS	
Interior	25 <sup>1</sup> / <sub>4</sub> "W x 17 <sup>1</sup> / <sub>2</sub> "H x 19 <sup>7</sup> / <sub>8</sub> "D
AHAM Overall Capacity	5.1 cu ft each
AHAM Usable Capacity	3.2 cu ft each
ELECTRICAL	
Supply	240/208 VAC, 60 Hz
Service	50 amp circuit
Conduit	5'


Specifications are subject to change without notice. Visit [wolfappliance.com/specs](http://wolfappliance.com/specs) for the most up-to-date information.

Dimensions may vary ±1/8" (3). Dimensions in parentheses are millimeters unless otherwise specified.

## DIMENSIONS




## STANDARD INSTALLATION



NOTE: Location of electrical supply within opening may require additional cabinet depth.

## FLUSH INSET INSTALLATION



\*1" (25) minimum depth. Shaded areas will be visible and should be finished to match cabinetry.  
 \*\*7/8" (22) for professional and transitional models and 1" (25) for contemporary model.  
 \*\*\*Dimension provides minimum reveals.

NOTE: Location of electrical supply within opening may require additional cabinet depth.