

PW482418

FEATURES

- _____ Rigorously tested for decades of use
- _____ Exceptional support from our Customer Care team in Madison
- _____ Heavy-duty stainless steel construction
- _____ Blower required (internal, in-line or remote blowers available)
- _____ Handfinished with hemmed edges and welded seams
- _____ Recessed controls for sleeker look
- _____ Infinite speed blower control
- _____ Heat sentry for safety
- _____ Bright halogen lighting
- _____ Transition with backdraft minimizes backward flow of cold air

ACCESSORIES

- _____ 1100 CFM Inline Blower
- _____ 1200 CFM Internal Blower
- _____ 1200 CFM Remote Blower
- _____ 1500 CFM Remote Blower
- _____ 18" Duct Cover
- _____ 36" Duct Cover
- _____ 400 CFM Internal Blower
- _____ 6" Duct Cover
- _____ 800 CFM Internal Blower
- _____ Backsplash
- _____ Backsplash with Warming Racks
- _____ Horizontal Discharge Kit
- _____ Make-Up Air Damper

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PW482418
Dimensions	48"W x 18"H x 24"D
Weight	94 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

