

## PWC362418

### FEATURES

Rigorously tested for decades of use

Exceptional support from our Customer Care team in Madison

Heavy-duty stainless steel construction

Blower required (internal, in-line or remote blowers available)

Bright halogen lighting

Heat sentry for safety

Recessed controls for sleeker look

Transition with backdraft minimizes backward flow of cold air

Infinite speed blower control

Install with accessory duct cover for chimney-style hood

Handfinished with hemmed edges and welded seams

### ACCESSORIES

1100 CFM Inline Blower

1200 CFM Internal Blower

1200 CFM Remote Blower

1500 CFM Remote Blower

30" Duct Cover

36" Duct Cover

400 CFM Internal Blower

800 CFM Internal Blower

Backsplash

Backsplash with Warming Racks

Make-Up Air Damper

38" high stainless steel backsplash with or without warming racks

Accessories available through an authorized dealer.

For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).




### BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

**PRODUCT SPECIFICATIONS**

Model	PWC362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

**ELECTRICAL**



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

**DIMENSIONS**

