

**PWC422418****FEATURES**

- Rigorously tested for decades of use
- Exceptional support from our Customer Care team in Madison
- Heavy-duty stainless steel construction
- Blower required (internal, in-line or remote blowers available)
- Bright halogen lighting
- Heat sentry for safety
- Recessed controls for sleeker look
- Transition with backdraft minimizes backward flow of cold air
- Infinite speed blower control
- Install with accessory duct cover for chimney-style hood
- Handfinished with hemmed edges and welded seams

**ACCESSORIES**

- 1100 CFM Inline Blower
- 1200 CFM Internal Blower
- 1200 CFM Remote Blower
- 1500 CFM Remote Blower
- 36" Duct Cover
- 400 CFM Internal Blower
- 800 CFM Internal Blower
- Backsplash
- Backsplash with Warming Racks
- Make-Up Air Damper
- 38" high stainless steel backsplash with or without warming racks

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](https://subzero-wolf.com/locator).


**BLOWER OPTIONS**

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

## PRODUCT SPECIFICATIONS

Model	PWC422418
Dimensions	42"W x 18"H x 24"D
Weight	86 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

## ELECTRICAL



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

## DIMENSIONS

