

PWC482418

FEATURES

- Rigorously tested for decades of use

- Exceptional support from our Customer Care team in Madison

- Heavy-duty stainless steel construction

- Blower required (internal, in-line or remote blowers available)

- Bright halogen lighting

- Heat sentry for safety

- Recessed controls for sleeker look

- Transition with backdraft minimizes backward flow of cold air

- Infinite speed blower control

- Install with accessory duct cover for chimney-style hood

- Handfinished with hemmed edges and welded seams

ACCESSORIES

- 1100 CFM Inline Blower

- 1200 CFM Internal Blower

- 1200 CFM Remote Blower

- 1500 CFM Remote Blower

- 36" Duct Cover

- 400 CFM Internal Blower

- 800 CFM Internal Blower

- Backsplash

- Backsplash with Warming Racks

- Make-Up Air Damper

- 38" high stainless steel backsplash with or without warming racks

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.




BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PWC482418
Dimensions	48"W x 18"H x 24"D
Weight	94 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

